

Cable for industrial electronics

JE-Y(St)2YYw



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: For signal transmission between electronic devices, in computer systems, process control units or office equipment. For installation in dry and wet rooms.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 1 = solid
Insulation:	PVC
Stranding unit:	pair
Stranding:	Bundle
Core wrapping:	plastic foil
Material inner sheath:	polyethylene
Screen:	plastic coated aluminium foil + solid copper drain wire
Sheathing material:	PVC
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Permitted outer cable temperature, fixed, °C:	-30 - +90 °C
Permitted outer cable temperature, moved, °C:	-5 - +70 °C
Bending radius, fixed installation:	10 x Ø
Impedance:	320 Ohm
Insulation resistance:	100 MOhm \times km
Specific inductivity:	0.65 mH/km



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

JE-Y(St)2YYw

Loop resistance: 73.2 Ohm/km
Maximum operating capacity: 100 nF/km
Core identification: colours + rings
Attenuation at 800 Hz: 0.11

part no.	part name	Ø [mm]	Cu [kg/km]	G [kg/km]
100963	02X2X0,8 BL	7.7	25	62
100965	04X2X0,8 BL	9.8	45	100
101400	16X2X0,8 BL	14.4	166	275
101402	20X2X0,8 BL	16	206	340
100844	32X2X0,8 BL	21	327	530
100964	02X2X0,8 SW	7.7	25	65
100966	04X2X0,8 SW	9.8	45	100
101401	16X2X0,8 SW	14.4	166	275
101403	20X2X0,8 SW	16	206	340
100983	32X2X0,8 SW	21	327	530

Ø | outer diameter approx.

Cu | Copper weight (GER)

G | net weight