

Profi-bus cable L2-FIP, DP, FMS 150 Fast Connect UL/CSA



conductor material:	bare copper
conductor construction:	Strand, 7-wired construction
insulation:	foam-skin
screen:	aluminium-foil + copper-braiding, tinned
sheathing material:	PVC
colour of outer sheath:	violet
flame retardant:	VDE 0482-332-1-2/IEC 60332-1-2
max. operating temperature,	-40 - +80 °C
fixed:	
bending radius, fixed	8 x DA
installation:	
impedance:	150 Ohm
operating capacity:	30 nF/km
loop resistance:	110 Ohm/km
nominal voltage U:	250 V
core identification:	red, green

Application: PROFIBUS is an international Fieldbus-standard for universal application in factory and process automation. For fixed indoor installation.



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Table: Technical characteristics FIELD- and PROFIBUS cable

p/n	part name	D _A [mm]	Cu [kg/km]	G [kg/km]
101301	Profibus PVC L2/FIP/DP/ FMS Fast Connect, cUL 01X2X0,64/7 VL	7,9	26	73

DA	outer diameter
Cu	copper weight (ger)
G	weight